PRODUCT SPECIFICATIONS 380 ALPR CAMERA-READY TRAILER



The trailer is compatible, interchangeably, with the following signage:

- SpeedAlert 18 or 24 (SA18 or SA24) Radar Message Sign
- InstAlert 18 or 24 (IA18 or IA24) Variable Message Sign
- Shield 15 (Sh15) Radar Speed Sign
- 5' clearance from the ground to bottom of the sign
- Meets Federal Department of Transportation MUTCD specifications

Features

- 1200 lb with 900Ah battery capacity and SpeedAlert 24
- Tongue weight: 96 lb
- **Dimensions:** 61.5" long x 62.5" wide x 66.5" high (stowed)
- Simple manual lever with lift-assist system for 1-person set-up
- Removable tongue for 2" ball, lockable
- Storage for tongue and lift bar in locked battery compartment
- 16 ga. steel locking battery compartment with vented battery chamber, charger/accessories chamber and 1/8" aluminum diamond plate lid
- Continuous weld steel frame, white marine grade powder coat finish
- Additional locking battery box for expanded battery capacity, includes ALPR system equipment area with access panel and optional recessed camera compartment
- Wheels: 12" bolt steel rims with 4.5" bolt circle
- **Ground Clearance:** 9.75 under axle, 19 under chassis
- Replaceable steel fenders, weight supporting
- Locking wheel lug bolts, one (1) per wheel, with removal tool
- Axle: 2000 lb leaf spring
- Jacks: 4, retractable crank type, fully adjustable at



each corner, 1500 lb capacity each

- Recessed tail lights and DoT approved lighting
- Safety chains, 23" with hooks
- DoT approved red/white reflective tape
- License plate holder with light

Trailer Power

- 12VDC system, standard four pin wiring plug
- 900Ah batteries, (2) 6VDC batteries in series, deep cycle marine (130 lb per pair, four (4) pairs)
- 40A time delay fuse on battery supply
- 380W solar assist with 30A MPPT solar controller with low voltage disconnect to prevent overcharging and over-discharging
- Solar panels charge while sign stowed or deployed
- 40 Amp 120VAC automatic charger with externally accessible AC connection
- Independent switches to control power to sign and ALPR system separately

Optional Components and Features

- External camera box (up to two (2) camera capacity)
- Recessed camera compartment
- 30" x 36" speed limit sign and interchangeable digits for 5-65 mph display and locking hitch pin for display and stowing; digit storage in battery compartment
- '7' digit for speed limit sign
- Red and blue violator strobe light bar, set to flash above user set speed
- 2 5/16" ball coupler or pintle hook, adjustable height,
- on removable tongue
- Orange powder coat finish (minimum order quantity)
- Tamper alarm with adjustable sensitivity
- Wheel lock bar
- 14" tires and fenders

Premier Care Warranty

One (1) year warranty (three (3) months on batteries)



Optional recessed camera compartment





For more information visit us online at AllTrafficSolutions.com

🖻 sales@alltrafficsolutions.com 🛛 🚺 Call us at 866.366.6602

All Traffic Solutions. 14201 Sullyfield Circle, Suite 300, Chantilly, VA 20151

©All Traffic Solutions TraffiCloud leverages our patented technology (US Patents 8417442; 8755990; 9070287; 9411893) to deliver unique cloud-based management, features and functionality. TraffiCloud is a registered trademark of All Traffic Solutions.



